



### Model T6000 I/P, E/P Transducer

Aluminum Body, Buna-N diaphragm, voice coil design, mA and voltage inputs

2.5 scfm flow capacity (standard range), 9.0 scfm flow capacity (extended range)

<u>Part No.</u>	<u>Connector</u>	<u>Output</u>	<u>Price</u>
TA6000-401	Conduit	3-15 psi	327.92
TA6000-402	Conduit	3-27 psi	327.92
TA6000-403	Conduit	3-30 psi	327.92
TA6000-404	Conduit	0-30 psi	395.65
TA6000-405	Conduit	0-60 psi	395.65
TA6000-406	Conduit	0-120 psi	395.65
TT6000-401	Term. Strp.	3-15 psi	335.08
TT6000-402	Term. Strp.	3-27 psi	335.08
TT6000-403	Term. Strp.	3-30 psi	335.08

<u>Part No.</u>	<u>Connector</u>	<u>Output</u>	<u>Price</u>
TT6000-404	Term. Strp.	0-30 psi	404.12
TT6000-405	Term. Strp.	0-60 psi	404.12
TT6000-406	Term. Strp.	0-120 psi	404.12
TD6000-401	DIN	3-15 psi	341.64
TD6000-402	DIN	3-27 psi	341.64
TD6000-403	DIN	3-30 psi	341.64
TD6000-404	DIN	0-30 psi	409.13
TD6000-405	DIN	0-60 psi	409.13
TD6000-406	DIN	0-120 psi	409.13