



Model T7800 I/P, E/P Transducer

Aluminum Body, Buna-N diaphragm, piezoresistive disc design, mA and voltage inputs
2.5 scfm flow capacity (standard range), 9.0 scfm flow capacity (extended range)

<u>Part No.</u>	<u>Connector</u>	<u>Output</u>	<u>Price</u>
TA7800-401	Conduit	3-15 psi	442.02
TA7800-402	Conduit	3-27 psi	442.02
TA7800-403	Conduit	3-30 psi	442.02
TA7800-404	Conduit	0-30 psi	535.68
TA7800-405	Conduit	0-60 psi	535.68
TA7800-406	Conduit	0-120 psi	535.68
TT7800-401	Term. Strp.	3-15 psi	453.81
TT7800-402	Term. Strp.	3-27 psi	453.81
TT7800-403	Term. Strp.	3-30 psi	453.81

<u>Part No.</u>	<u>Connector</u>	<u>Output</u>	<u>Price</u>
TT7800-404	Term. Strp.	0-30 psi	549.93
TT7800-405	Term. Strp.	0-60 psi	549.93
TT7800-406	Term. Strp.	0-120 psi	549.93
TD7800-401	DIN	3-15 psi	465.72
TD7800-402	DIN	3-27 psi	465.72
TD7800-403	DIN	3-30 psi	465.72
TD7800-404	DIN	0-30 psi	564.24
TD7800-405	DIN	0-60 psi	564.24
TD7800-406	DIN	0-120 psi	564.24